



Have an unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone

High tensile strength

Non-flammability

Operating temperature:-40°C-85°C

High resistance to acetic acid,alkali acid, sulphuric acid,corrode,etc

All length/ colour are available stainless steel 304#,316#

Part No.	Approx.Length mm(inch)	Approx.Width mm(inch)	Max.Bundle Dia mm(inch)	Mini.Loop Tensile Strength N(lbs)
FZOSP-12X150	150(5.9)	12(0.47)	37(1.46)	1200(270)
FZOSP-12X200	200(7.87)		50(1.97)	
FZOSP-12X250	250(9.84)		63(2.48)	
FZOSP-12X300	300(11.8)		76(2.99)	
FZOSP-12X350	350(13.78)		89(3.5)	
FZOSP-12X400	400(15.75)		102(4.02)	
FZOSP-12X450	450(17.72)		115(4.53)	
FZOSP-12x500	500(19.69)		128(5.04)	
FZOSP-12X550	550(21.65)		141(5.55)	
FZOSP-12X600	600(23.62)		154(6.06)	
FZOSP-12x650	650(25.6)		167(6.57)	
FZOSP-12X700	700(27.6)		180(7.09)	
FZOSP-12X800	800(31.5)		193(7.59)	
FZOSP-15X200	200(7.87)	15(0.59)	50(1.97)	1500(337)
FZOSP-15X250	250(9.84)		63(2.48)	
FZOSP-15X300	300(11.8)		76(2.99)	
FZOSP-15X350	350(13.78)		89(3.5)	
FZOSP-15X400	400(15.75)		102(4.02)	
FZOSP-15X450	450(17.72)		115(4.53)	
FZOSP-15X500	500(19.69)		128(5.04)	
FZOSP-15X550	550(21.65)		141(5.55)	
FZOSP-15X600	600(23.62)		154(6.06)	
FZOSP-15X650	650(25.59)		167(6.57)	
FZOSP-15X700	700(27.56)		180(7.09)	
FZOSP-15X750	750(29.53)		191(7.52)	
FZOSP-15X800	800(31.5)		193(7.59)	
FZOSP-15X1000	1000(39.37)	206(8.11)		