



High tensile strength; Non-flammability

Working temperature: -40°C-85°C

High resistance to acetic acid, alkali acid, sulphuric, corrode, etc

All length are available, stainless steel 304#, 316#

Part No.	Approx.Length mm(inch)	Approx.Width mm(inch)	Max.Bundle Dia mm(inch)	Mini.Loop Tensile Strength N(lbs)
FZLSJ-9X150	150(5.9)	9(0.35)	37(1.46)	800(180)
FZLSJ-9X200	200(7.87)		50(1.97)	
FZLSJ-9X250	250(9.84)		63(2.48)	
FZLSJ-9X300	300(11.8)		76(2.99)	
FZLSJ-9X350	350(13.78)		89(3.5)	
FZLSJ-9X400	400(15.75)		102(4.02)	
FZLSJ-9X450	450(17.72)		115(4.53)	
FZLSJ-9X500	500(19.69)		128(5.04)	
FZLSJ-9X600	600(23.62)		141(5.55)	
FZLSJ-9X650	650(25.59)		167(6.57)	
FZLSJ-9X700	700(27.56)		180(7.09)	
FZLSJ-13X150	150(5.9)	13(0.51)	37(1.46)	1200(270)
FZLSJ-13X200	200(7.87)		50(1.97)	
FZLSJ-13X250	250(9.84)		63(2.48)	
FZLSJ-13X300	300(11.8)		76(2.99)	
FZLSJ-13X350	350(13.78)		89(3.5)	
FZLSJ-13X400	400(15.75)		102(4.02)	
FZLSJ-13X450	450(17.72)		115(4.53)	
FZLSJ-13X500	500(19.69)		128(5.04)	
FZLSJ-13X550	550(21.65)		141(5.55)	
FZLSJ-13X600	600(23.62)		154(6.06)	
FZLSJ-13X650	650(25.59)		167(6.57)	
FZLSJ-13X700	700(27.56)	180(7.09)		
FZLSJ-16X200	200(7.87)	16(0.63)	50(1.97)	1500(337)
FZLSJ-16X250	250(9.84)		63(2.48)	
FZLSJ-16X300	300(11.8)		76(2.99)	
FZLSJ-16X350	350(13.78)		89(3.5)	
FZLSJ-16X400	400(15.75)		102(4.02)	
FZLSJ-16x450	450(17.72)		115(4.53)	
FZLSJ-16X500	500(19.69)		128(5.04)	
FZLSJ-16X550	550(21.65)		141(5.55)	
FZLSJ-16X600	600(23.62)		154(6.06)	
FZLSJ-16X650	650(25.59)		167(6.57)	
FZLSJ-16X700	700(27.56)		180(7.09)	