



High tensile strength; Non-flammability

Working temperature: -60°C - 150°C

High resistance to acetic acid, alkali acid, sulphuric, corrode, etc

All length are available, stainless steel 304#, 316#

Part No.	Approx.Length mm(inch)	Approx.Width mm(inch)	Max.Bundle Dia mm(inch)	Mini.Loop Tensile Strength N(lbs)
JZLS-12X150	150(5.9)	12(0.47)	37(1.46)	1200(270)
JZLS-12X200	200(7.87)		50(1.97)	
JZLS-12X250	250(9.84)		63(2.48)	
JZLS-12X300	300(11.8)		76(2.99)	
JZLS-12X350	350(13.78)		89(3.5)	
JZLS-12X400	400(15.75)		102(4.02)	
JZLS-12X450	450(17.72)		115(4.53)	
JZLS-12X500	500(19.69)		128(5.04)	
JZLS-12X550	550(21.65)		141(5.55)	
JZLS-12X600	600(23.62)		154(6.06)	
JZLS-12X650	650(25.6)		167(6.57)	
JZLS-12X700	700(27.6)		180(7.09)	
JZLS-12X800	800(31.5)		193(7.59)	
JZLS-15X200	200(7.87)		15(0.59)	
JZLS-15X250	250(9.84)	63(2.48)		
JZLS-15X300	300(11.8)	76(2.99)		
JZLS-15X350	350(13.78)	89(3.5)		
JZLS-15X400	400(15.75)	102(4.02)		
JZLS-15X450	450(17.72)	115(4.53)		
JZLS-15X500	500(19.69)	128(5.04)		
JZLS-15X550	550(21.65)	141(5.55)		
JZLS-15X600	600(23.62)	154(6.06)		
JZLS-15X650	650(25.59)	167(6.57)		
JZLS-15X700	700(27.56)	180(7.09)		
JZLS-15X750	750(29.53)	191(7.52)		
JZLS-15X800	800(31.5)	193(7.59)		
JZLS15X1000	1000(39.37)	206(8.11)		